



Security Through Innovation

EASICALL COMPACT

Entrance Panel



Our Easicall Compact range of entrance panels are robustly constructed from **316L Marine Grade Stainless Steel** to remain resilient to attack and withstand even the most aggressive atmospheric conditions.

To resist vandalism attempts **apertures are no greater than 3mm in depth** with stainless steel mesh included between internal components and the panel plate for added protection.



Reader Position

Integrate an electronic Access Control System for simple resident access management

Compact Design

Offers a neat solution

Security Fixings

Robust construction for vandal resistance

Fitting Styles

Customise the finish of your panel on the building fabric with a choice of overlap, bezel and surface mounted designs
(Overlap style shown here)

Microphone

Minimises outdoor background noise providing clear two-way communication between visitor and resident

High Quality Speaker

Provides clear audio feedback of system operation

Laser Etching & Braille

Customise functional information including flat numbers, block name, operating instructions and associated buttons

Press and wait for reply

Functional Layout

A call button is allocated to each dwelling
(Click-Touch Buttons shown here)

Trades Facility

Set timed periods for trades entry such as postal delivery

5mm lexan windows are used to protect displays and readers from shattering in the event of being exposed to heavy impacts or high temperatures.

For increased security, the panel is **front fixed with 5mm stainless steel tamper resistant counter sunk security screws**, requiring the use of a special key for removal or re-fitting.

Specifications

EASICALL COMPACT Entrance Panel

Technical

Compatible Door Entry System: Easicall
Number of Flats: 1 - 12 plus Trades
Number of Entrance Panels per System: 1
Audio: Yes
Video: No
Power: 12V DC Input
Temperature: Operating -20°C to 80°C
Storage: -40°C to 80°C

Laser Etched Characters

Colour: Black
Size: 6mm (24 point) minimum

Braille

Where required
Type: Grade II Standard English
Availability: Flat Numbers
Block Name
Operating Instructions

Call Buttons

Functional Layout: 1 call button per dwelling
Stainless Steel with contrasting yellow ring
Cut-out Diameter: 19.2mm
Laser engraved characters on panels or buttons options
Button Types:
Vandal Resistant (VRB): Provides tactile feedback of input
ingress less than 3mm to protect
from vandalism
Click-Touch (CTBYR): Vandal resistant button with stainless
steel actuator and zinc diecast yellow
varnished housing
(characters engraved on button option)

Trades Facility

Where required
Optional engraving
Programmable via GMT/BST Time Clock

Speaker Amp & Microphone

Split Speaker Amplifier and Microphone
Frequency Range: 250 Hz to 10k Hz
Adjustable speaker volume and microphone gain
Maximum volume with minimum feedback

Reader Position

Where required
Integrate Access Control: KMS
Choice of Readers

Additional Options

Engraved Corporate Logos



Overlap style shown on above panel
with Click-Touch Buttons

DDA Additions

A range of features are available to aid visitors with disabilities:

- Contrasting yellow rings around buttons to distinguish from stainless steel of call panel
- Yellow contrasting reader with tactile key symbol
- Braille flat numbering, block name and operating instructions available
- Audible feedback of operation



Dimensions

EASICALL COMPACT Entrance Panel

Overlap

Cutout Dimensions (minimum):
252 H x 139 W x 62 D (mm)



Please contact our Sales Department for entrance panel or backbox dimensions.

Bezel

Cutout Dimensions (minimum):
263 H x 148 W x 64 D (mm)



Surface Mount

Box Dimensions:
253 H x 140 W x 67mm D (mm)

