

Video Handset

EXPERIENCE

Entrotec has over 25 years of experience in the design and manufacture of vandal resistant door entry systems.

WARRANTY

Entrotec systems are renowned for their reliability and have a 2 year warranty on all Entrotec manufactured products as standard.

SUPPORT

Entrotec offer complimentary training courses and telephone support.



- H = 185mm W = 190mm D = 50mm
- High Resolution Colour TFT-LCD Display
- Multiple Viewing Angle (MVA) Display
- Illuminated Privacy Button
- Illuminated Door Open Button
- User Adjustable Call Tone Volume
- Easy Installation with Low Profile Wall Mounting Plate

Technical Specification

Display	4.3" (diagonal) widescreen 480x272 pixel resolution Viewing Angle: L-60°, R-60°, U-50°, D-55° 350:1 contrast ratio (typical) 300 cd/m2 max brightness (typical)
Call Tone	3 position slide switch volume adjustment 85.4dB SPL max (at 1 metre)
Privacy	Illuminated button to indicate privacy status (red on) Latch on/off (no timeout)
Door Open	Illuminated button to indicate door status (green on)

Power	175mA peak at 13.8VDC 7mA quiescent at 13.8VDC
Video	Easy setup with On Screen Display (OSD) adjustments Twisted pair transmission with high noise immunity
Cable	CAT5 up to 50m (with internally generated call tone) 6 Pair CW1308 minimum up to 50m 10 Pair CW1308 minimum if exceeding 50m
Accessories	Optional extension Sounder or Beacon available Optional pattress to accommodate surface cabling in mini-trunking

Entrotec Limited
5 Ashwood Court
Oakbank
Livingston
EH53 0TL

www.entrotec.com
Tel: +44(0) 1506 886230
Fax: +44(0) 1506 886233
saleshq@entrotec.co.uk
Support: 0844 858 6370

